


HSD10 DTH HAMMER

HSD10 DTH HAMMER	Item Description	Weight (Kg)	Part Number
	1 Top sub	63.0	HSD10-TSUB
	2 O ring of Top sub x1	0.05	HSD10-SK-TSUB
	3 Breakout Ring of Top sub	1.20	HSD10-TSUB-BRING
	4 Check Valve	1.50	HSD10-CVALVE
	5 Spring	0.20	HSD10-SPRING
	6 Air Distributor	13.0	HSD10-DIST
	7 Internal Cylinder	13.6	HSD10-ICYL
	8 Piston	68.0	HSD10-PISTON
	9 External Cylinder	92.5	HSD10-ECYL
	10 Retaining ring	0.60	HSD10-RRING
	11 O ring of Stop Ring x1	0.05	HSD10-SK-SRING
	12 Stop Ring	2.80	HSD10-SRING
	13 Guided Sleeve	5.00	HSD10-GSLEEVE
	14 Breakout Ring of Drive chuck	1.20	HSD10-DCHUCK-BRING
	15 Drive chuck	23.5	HSD10-DCHUCK
	16 Drill Bit		

Technical Data

Length(Less bit)	Weigth(Less bit)	External Diameter	Bit Shank	Hole Range	Connection Thread
1413mm	303kg	Φ225mm	SD10	Φ254-Φ305mm	API 6 5/8 " REG
Box Size	Impact rate at 2.4Mpa	Recommended rotation speed	Air Consumption		
			300-380(PSI)		
1620*275*290mm	20HZ	15-35 RPM	950-1200(CFM)		