

NUMA125-R RETENTION DTH HAMMER

NUMA125-R Hammers		Item Description	Weight (Kg)	Part Number
	1	Top Sub	123.0	HN125-TSUB
	2	"O" Ring of Top Sub	0.02	HN125-SK-TSUB
	3	Breakout Ring of Top Sub	0.85	HN125-MURS-TSUB
	4	Check Valve	1.00	HN125-CVALVE
	5	Spring	1.00	HN125-SPRING
	6	Air Distributor	20.20	HN125-DIST
	7	Internal Cylinder	31.00	HN125-ICYL
	8	Piston	111.0	HN125-PISTON
	9	External Cylinder	147.0	HN125-ECYL
	10	Bush	18.4	HN125-BUSH
	11	Bush Retaing Ring	0.20	HN125-BUSH-RRING
	12	Stop Ring	5.30	HN125-SRING
	13	"O"Ring of Stop Ring	0.02	HN125-SK-SRING
	14	Lock Pin	0.20	HN125-LOCK-PIN
	15	Nylon Strip	0.30	HN125-STRIP-NYLON
	16	Internal Bit Catcher	6.80	HN125-IBCATCHER
	17	External Bit Catcher	15.7	HN125-EBCATCHER
	18	Drive Chuck	31.9	HN125-DCHUCK
	19	Plastic Spacer of Drive Chuck	0.5	HN125-PSPACER
	20	Bit		N125-476CC

Technical Data

Length(Less bit)	Weigth(Less bit)	External Diameter	Bit Shank	Hole Range	Connection Thread
1812mm	546kg	Φ275mm	NUMA125R	Φ305-Φ445mm	API 6 5/8 "REG
Box Size	Impact rate at 1.7Mpa	Recommended rotation speed	Air Consumption		
			200-350(PSI)		
1880x310x310mm	18HZ	15-35r/min	800-1800(CFM)		