

## Product

## Black Diamond Rock Drill Oil

## Summary

## Product description

Black Diamond Rock Drill Oil is a range of lubricants formulated with highly refined mineral oils and a combination of additives, including extreme pressure, tackiness and antifoaming additives, rust and corrosion inhibitors, and emulsifiers. Designed for the lubrication and cooling of pneumatically operated rock drills in underground and surface-mining operations, they are also suitable for the lubrication of similar equipment in building and highway construction applications. Available in seven viscosity grades: from ISO 32 to ISO 320.


### Available sizes



5L



PAIL – 20L



DRUM – 200L



IBC – 1000L

Also  
available  
in bulk

## Applications

Black Diamond Rock Drill Oil is suitable for use in:

- Pneumatically operated rock drills used in both underground and surface-mining.
- Pneumatically operated drills, jack hammers and tampers used in highway construction and building.
- Rock drills used in quarrying.
- Percussion and rotary air-operated tools in other industrial uses.

## Features and benefits

- Good lubrication and cooling properties, along with excellent extreme pressure and antiwear performance, protect drill parts from wear, even under the severe conditions of continuous shock loading, and lead to longer component life.
- A tackiness additive provides excellent adhesive properties and ensures that the oil clings to moving parts and is not easily flung or washed off, giving lower oil consumption and longer drill life.
- Rust and corrosion inhibitors protect metals parts, even when constantly exposed to moisture or corrosive environments.
- Good emulsifying properties prevent water from displacing the oil and wetting metal surfaces, and so ensure a good oil film is maintained protecting surfaces against wear and also preventing corrosion.
- Available in a range of viscosity grades, to enable the selection of a single grade that will suit year-round use even where seasonal ambient temperatures vary widely.
- Meet the performance requirements of many rock drill manufacturers.

# Product Data Sheet

## Typical data

<b>Black Diamond Rock Drill Oil</b>							
ISO viscosity grade	32	46	68	100	150	220	320
Kinematic viscosity, ASTM D 445							
cSt @ 40°C	32.0	46.0	68.0	100.0	150.0	220.0	320.0
cSt @ 100°C	5.34	6.72	8.61	11.1	14.61	18.44	23.69
Viscosity index, ASTM D 2270	97	97	96	95	95	92	93
Copper corrosion, 3 hours @ 100°C, ASTM D 130	1b	1b	1b	1b	1b	1b	1b
Pour point, °C, ASTM D 97	-27	-24	-21	-18	-18	-12	-12
Flash point (COC), °C, ASTM D 92	212	218	225	222	238	238	242
Density @ 15°C, kg/l, ASTM D 4052	0.847	0.854	0.863	0.872	0.879	0.884	0.895

These data are given as an indication of typical values, not as exact specifications.

## Industry and OEM specifications

<b>Black Diamond Rock Drill Oil meets the performance requirements of the following OEM specifications:</b>	
Gardner Denver	Light, medium and heavy rock drill oils
Ingersoll-Rand	Light, medium and heavy rock drill oils

## Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Black Diamond guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Black Diamond cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

## Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Material Safety Data Sheet (MSDS) is followed. Please consult the MSDS for more detailed advice on handling; MSDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The **Black Diamond** trademark is registered and protected in Australia.

Issued: May 2017

© Black Diamond 2017