

BD Drill Surface Drilling Top Hammer Drilling Tools

www.bddrill.com.au / www.bddrill.ca





Black Diamond Drilling Services Australia Pty Ltd

ABOUT US

1000

EMPLOYEES

Black Diamond Drilling Services Australia Pty Ltd

WA Headquarters: 52 Distinction Road, Wangara WA 6065

Tel: +61-08-6365-6550 Email: sales@bddrill.com.au Web: www.bddrill.com.au Kalgoorlie Branch: 2 Brooks Way, Kalgoorlie, WA, 6430

Tel: +61-08-9021-8478 Email: admingf@bddrill.com.au Web: www.bddrillgf.com.au

Black Diamond Drilling Tools Canada Inc.


Sudbury Headquarters: 1899 Lassalle Blvd, unit 6, Sudbury, On, Canada, P3A-2A3 Tel: +1-705-560-5888 Email: sales@bddrill.ca Web: www.bddrill.ca

Black Diamond Drilling Tools USA LLC.

New Hampshire Headquarters: 131 Daniel Webster Hwy, #426 Nashua, NH 03060 **Tel:** +1-978-319-8000 **Email:** sales@bddrill.us **Web:** www.bddrill.us

Black Diamond Drilling Mongolia LLC.

Ulan Bator Headquarters: No 206, Second Floor, Arig Center Jamyan Gun Street, 1st Khoroo, Sukhbaatar District, Ulaanbaatar, Mongolia **Tel:** +976-99623888 **Email:** sales@bddrilling.mn



Maximum size for drill bit: 1000mm(39-1/3") 30 days for production on any quantity


Black Diamond Drilling Services Australia Pty Ltd known as "BD DRILL" is a privately owned Australian Company which services the Mineral exploration, Mining, Water well and Geotechnical sectors of the drilling industry.

BD DRILL is a subsidiary of Changsha Heijingang Industrial Ltd. Co., the head office is located in Perth, Western Australia and supports regions in Australia and the overseas market.

BD DRILL has established a reputation for outstanding commitment to product quality, innovation and most importantly customer service.

Our extensive product range covers DTH equipment (conventional, reverse circulation, bits, strings and rigs), Top hammer and a comprehensive selection of various drilling products (diamond bit, drag bit, tricone bits, drilling grease and other consumables.)











RECOMMENDED SAFETY PROCEDURES

The mining industry continues to demand even higher levels of safety and productivity. In order to meet these requirements, we work continuously to develop even safer products and to produce comprehensive manuals enabling safer and effective use of our products.



IT'S ALL ABOUT EVERYONE'S HEALTH

Helping you to ensure a safer workplace and healthier workforce is of the utmost importance to us. The wellbeing of any person coming into contact with our equipment is paramount. Therefore, we strive to identify and assess potential risk factors that could threaten the health of you and your employees. All the products in our catalogue are designed to meet safety requirements.

DRESS RIGHT FROM HEAD TO TOE

You must always wear appropriate personal protective equipment (PPE). This is what we strongly recommend, to help avoid injury:

- Safety helmet
- Hearing protection
- Safety glasses
- Protective high visibility clothing
- Respiratory protection
- Safety boots
- Any site-specific PPE as required

BE AWARE OF ALL SAFETY PROCEDURES

We ask that you start by obeying all instructions given. Never work under an unsupported rood or close to potential pinch point locations. Beware of the potential hazards of a loose roof and ribs and scale down roof ribs prior to bolting. It is important to bolt early in the mining process – as soon is safely and practically possible.


Safe work procedures should incorporate inspection before the machine operates and also through regular monitoring based upon mining conditions, safety and management systems. Workers should be provided with safety information, instruction and training on transportation, installation, operational care and disposal of drilling tools.

MAKE A RISK ANALYSIS BEFORE YOU START

Pay attention to safety when planning all of your work. Before you start, always take your time to go through all operations. Identify any potential risks and take appropriate measures to avoid them. If necessary, seek expert advice on how to help minimize risks. Finally, make sure that you have the right resources to perform all tasks in the safest manner possible.



TOP HAMMER DRILL STRING



T51 SURFACE DRILLING BITS

BITS	DIMENSIONS		Buttons, mm		Angle	Flushing Hole, mm		Part Number	Compatibility
	Imperia I	Metric	Front No Size	Gauge No Size		Front No Size	Gauge No Size		
	3 1/2"	89mm	6x10	8x11	35°	4x12	-	TH-R89FF8-T51-TK	90513764
	3 1/2"	89mm	6x12	8x14	40°	4x12	-	TH-R89DC8-T51-TK	90513813
	4"	102mm	6x14	8x14	35°	4x13	-	TH-N102FF8-T51-TV	90510807
i significant de la construcción de	4"	102mm	6X14	8x16	40°	4x14	-	TH-N102DC8-t51-TV	90510343
	4"	102mm	6x11	8x14	35°	4x14	-	TH-N102DC8-T51-TV-B	90510824
	4"	102mm	6x11	8x14	35°	2x12	-	TH-R102DC8-T51-TV/M	90510825
	4"	102mm	6x11	8x14	35°	2x12	-	TH-R102CVB-T51-TV	-
	4 1/2"	115mm	6x14	8x16	35°	2x13	-	TH-N115FF8-T51-TV	7516-1915-S48 90510340
	4 1/2"	115mm	6x14	9x14	35°	2x13	-	TH-N115DC8-T51-TV	90510874
	4 1/2"	115mm	7x14	9x14	35°	3x13	-	TH-R115FF9-T51-TV-M	90510344
	4 1/2"	115mm	7x14	9x14	35°	3x13	-	TH-R115DC-T51-TV-M	-
	4 1/2"	115mm	7x14	9x14	35°	3x13	-	TH-R115DC8-T51-TV-B	-
	4 1/2"	115mm	7x14	9x14	35°	3x13	-	TH-R115DC8-T51-TV-SB	-
	5"	127mm	6x14	8x16	35°	4x14	-	TH-N127FF8-T51-TV	90510360
	5"	127mm	6x14	8x16	35°	4x14	-	TH-N127DC8-T51-TV	90513815
	5"	127mm	6x14	8x16	35°	4x14	-	TH-N127CVB-T51-TV	7516-4927-S48 90513757
	5"	127mm	7x14	8x16	35°	2x14	-	TH-R127FF8-T51-TV	-
	5"	127mm	7x14	8x16	35°	2x14	-	TH-R127DC-T51-TV-M	7516-4927-S48 90513757
	5 1/2"	140mm	6x15	8x15	35°	2x15	-	TH-N140DC-T51-TV	90515254
	5 1/2"	140mm	7x15	9x15	35°	3x15	-	TH-R140DC8-T51-TV	90515254

EL60 SURFACE DRILLING BITS

BITS	DIMENSIONS		Buttons, mm		Angle	Flushing Hole, mm		Part Number
Biro	Imperial	Metric	Front Gauge No Size No Size		, ungio	Front No Size	Gauge No Size	
	4"	102mm	7x12	8x13	35°	2x12	-	TH-N102DC8-EL60-TV-SPH
	4"	102mm	6x12	8x13	35°	2x12	-	TH-R102DC8-EL60-TV-SPH
	4 1/2"	115mm	6X11	8X13	40°	4X12	-	TH-N115DC-EL60-TV
	4 1/2"	115mm	6x11	8x13	40°	4x12	-	TH-R115DC-EL60-TV
	5"	127mm	6X14	8X14	35°	2X13	-	TH-N127DC8-EL60-TV-SPH
	5"	127mm	6x14	8x14	35°	4x13	-	TH-R127DC8-EL60-TV-SPH
	5 1/2"	140mm	6X14	8X14	35°	4X14	-	TH-N140DC8-EL60-TV-SPH
	5 1/2"	140mm	7x14	9x14	35°	3x14	-	TH-R140DC8-EL60-TV-SPH

BT60 SURFACE DRILLING BITS

BITS	DIMENSIONS		Buttons, mm		Angle	Flushing Hole, mm		Part Number
	Imperial	Metric	Front No Size	Gauge No Size	Ŭ	Front No Size	Gauge No Size	
	4"	102mm	6x12	8X13	35°	4X12	-	TH-N102DC8-BT60-TV
	4"	102mm	6x12	8x13	35°	4x12	-	TH-R102DC8-BT60-TV
	4 1/2"	115mm	6X11	8X13	40°	2X12	-	TH-N115DC8-BT60-TV
	4 1/2"	115mm	7x11	9x13	40°	3x12	-	TH-R115DC8-BT60-TV-M

M/F SPEED RODS

		Dimensic	ns			
RODS	Lengt	h, L	Diam	eter	Part Number	Compatibility
	Imperial	Metric Imperial Metric				
T51						
i72 i52	12'	3660mm	2"	52mm	ROD-TH-T51-3660-MF-O	7326-5537-70 90515311
T51 L T51	14'	4300mm	2"	52mm	ROD-TH-T51-4300-MF	7326-5543-85 90515314
	20'	6100mm	2"	52mm	ROD-TH-T51-6100-MF-O	7326-5561-85 90515557
	24'	7300mm	2"	52mm	ROD-TH-T51-7300-MF	-
EL60						
100 + 60 + EL60 EL60	12'	3660mm	2 3/8"	60mm	ROD-TH-EL60-3660-MF	-
le [14'	4300mm	2 3/8"	60mm	ROD-TH-EL60-3660-MF	210250
	20'	6100mm	2 3/8"	60mm	ROD-TH-EL60-3660-MF	210268
	24'	7300mm	2 3/8"	60mm	ROD-TH-EL60-3660-MF	-
BT60						
	12'	3660mm	2 3/8"	60mm	ROD-TH-BT60-3660-MF	-
1 BT60 BT60	14'	4300mm	2 3/8"	60mm	ROD-TH-BT60-4300-MF	-
	20'	6100mm	2 3/8"	60mm	ROD-TH-BT60-6100-MF	-
	24'	7300mm	2 3/8"	60mm	ROD-TH-BT60-7300-MF	-



EXTENSION RODS

		Dimens	ions			
RODS	Len	gth, L	Diam	eter	Part Number	Compatibility
	Imperial	Metric	Imperial	Metric		
T51	11"	280mm	2"	52mm	ROD-TH-T51-280-MM	-
152 T51 † T51	3'	915mm	2"	52mm	ROD-TH-T51-915-MM	-
I	12'	3660mm	2"	52mm	ROD-TH-T51-3660-MM	7326-5337C-30 90515299
	14"	4300mm	2"	52mm	ROD-TH-T51-4300-MM	7326-5343C-30 90515300
	20'	6100mm	2"	52mm	ROD-TH-T51-6100-MM	7326-5361C-30 90515301
	24'	7300mm	2"	52mm	ROD-TH-T51-7300-MM	-
EL60	3'	915mm	2 3/8"	60mm	ROD-TH-EL60-915-MM	203011
	12'	3660mm	2 3/8"	60mm	ROD-TH-EL60-3660-MM	200529
	14"	4300mm	2 3/8"	60mm	ROD-TH-EL60-4300-MM	200530
	20'	6100mm	2 3/8"	60mm	ROD-TH-EL60-6100-MM	200543
	24'	7300mm	2 3/8"	60mm	ROD-TH-EL60-7300-MM	-
BT60	3'	915mm	2 3/8"	60mm	ROD-TH-BT60-915-MM	-
160 BT60 1 BT60	12'	3660mm	2 3/8"	60mm	ROD-TH-BT60-3660-MM	-
L	14"	4300mm	2 3/8"	60mm	ROD-TH BT60-4300-MM	-
	20'	6100mm	2 3/8"	60mm	ROD-TH-BT60-6100-MM	-
	24'	7300mm	2 3/8"	60mm	ROD-TH-BT60-7300-MM	-

T51 GUIDE TUBES

	Length		Diameter			
GUIDE TUBE	Imperial	Metric	Imperial	Metric	Part Number	Compatibility
T51						
176 176 76i	12'	3660mm	3"	76mm	TH-GTUBE-T51-3600-FF-76	-
+76 +76 +76 +76 +76 +76 +76 +76 +76 +76	12'	3660mm	3"	76mm	TH-GTUBE-T51-3600-MF-76	7957-7637-70 94502641
187 +87 1 EL60 + EL60	12'	3660mm	3 1/2"	87mm	TH-GTUBE-EL60-3660-MF-87	
ВТ60	14'	4300mm	3 1/2"	87mm	TH-GTUBE-EL60-4300-MF-87	270097
1 BT60 1 BT60	12'	3660mm	3 1/2"	87mm	TH-GTUBE-BT60-3660-MF-87	
	14'	4300mm	3 1/2"	87mm	TH-GTUBE-BT80-4300-MF-87	



COUPLING SLEEVES

			Dimensio	ons			
COUPLING SLEEVES	Thread	Length	, L	Diamet	er, D	Part Number	Compatibility
		Imperial	Metric	Imperial	Metric		
	T51	7 7/8"	225mm	2 51/64"	71mm	TH-COUP-T51	7316-3671
	T51	9 1/4"	235mm	3 1/32"	77mm	TH-COUP-T51- 77/SS235	90515743
	T51	9 1/4"	235mm	3 1/32"	77mm	TH-COUP-T51- 77/SS235-SB	90515745
	T51	9 1/4"	235mm	3 1/4"	82mm	TH-COUP-T51- 82/SS235-SB	-
	EL60	7 1/2"	190mm	2 13/32"	61mm	TH-COUP-EL60- 82/190-SB	-

SHANK ADAPTORS

SHANK ADAPTOR	Drifter Model	Thread	Length, L	Part Number	Compatibility
107.2 469.9 65 4 65 4	COP 4050ME	EL60	700mm	TH-SHANK-COP4050/S-T51	7600-3712-01
	COP3060	T45	830mm	TH-SHANK-T51- COP3060/T45	-
	COP2160EX/ 2560EX	T51	770mm	TH-SHANK-2160/2560EX-T51	7306-3689-01
	HPR2	T51	915mm	TH-SHANK-T51- HPR2/GD5000	-
	HPR2-60	T51	1040mm	TH-SHANK-HPR2-60-T51	-
	HPR2-60	EL60	1040mm	TH-SHANK-HPR2-60-EL60	-
	HPR2-70	T51	1040mm	TH-SHANK-HPR2-70-T51	-
	HD612	T45	720mm	TH-SHANK-HD612-T45	7305-3663-01
122 + 58 L 123	HD715	T51	885mm	TH-SHANK-HD715-T51	7306-7424-01
	HC120R	T45	670mm	TH-SHANK-HC120R-T45	90516212
	HC120R	T51	670mm	TH-SHANK-HC120R-T51	7306-7528-02
	HC160	T51	805mm	TH-SHANK-HC160R-T51	90516047
	HL700	T51	650mm	TH-SHANK-HL700/650	7305-6008-01
	HL1500	T51	760mm	TH-SHANK-T51-1500- D80/L760	7600-6022-03
	HL1500	BT60	760mm	TH-SHANK-BT60-1500- D65/L760	
	HL1500	BT60	760mm	TH-SHANK-BT60-1500- D80/L760	
	HL1500PE	T51	760mm	TH-SHANK-T51-1500PE- D65/L760	90003702

Black Diamond Drilling can custom manufacture equipment to suit your drilling needs. Please contact one of our representatives to discuss your equipment needs.



Black Diamond Drilling Services Australia Pty Ltd

WA Headquarters: 52 Distinction Road, Wangara WA 6065
Tel: +61-08-6365-6550 Email: sales@bddrill.com.au
Web: www.bddrill.com.au
Kalgoorlie Branch: 2 Brooks Way, Kalgoorlie, WA, 6430
Tel: +61-08-9021-8478 Email: admingf@bddrill.com.au
Web: www.bddrillgf.com.au

Black Diamond Drilling Tools Canada Inc.

Sudbury Headquarters: 1899 Lassalle Blvd, unit 6, Sudbury, On, Canada, P3A-2A3 Tel: +1-705-560-5888 Email: sales@bddrill.ca Web: www.bddrill.ca

Black Diamond Drilling Tools USA LLC.

New Hampshire Headquarters: 131 Daniel Webster Hwy, #426 Nashua, NH 03060 Tel: +1-978-319-8000 Email: sales@bddrill.com Web: www.bddrill.us

Black Diamond Drilling Mongolia LLC.

Ulan Bator Headquarters: No 206, Second Floor, Arig Center Jamyan Gun Street, 1st Khoroo, Sukhbaatar District, Ulaanbaatar, Mongolia **Tel:** +976-99623888 **Email:** sales@bddrilling.mn

Version 2

© Black Diamond Drilling Services Australia Pty. Ltd. 2024 Legal Notice: All trademarks and logos appearing in this material are owned by BDDrill Group of companies, unless specifically indicated.





